





公差等级/General Tolerances(mm)		5										6	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>280	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	>500	
3	6	10	18	30	50	80	120	180	280	315	400	500	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	



MATERIAL:	/	SURFACE:	/
MAT NO.:	/		
STATUS:	/		
APPD:	LonQhH 2020.05.18	NAME:	2EDGKR-5.08-XXP-1Y-00A(H)
CHKD:	GoqgYzh 2020.05.18	DRAWING NO.:	10002068
DRTF:	LY 2020.05.18	TYPE:	CUSTOMER DRAWING
REV	ECN	DESCRIPTION	DRTF
DATE	DATE	SCALE:	2:1
SIZE:	A4	SHEET	1/1

5	Screws	Steel	M2.5/Zn Plated
4	cage	Copper alloy	Ni Plated
3	Pin	Copper	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	/	320/20	/
额定冲击电压(kV)/Rate Impulse Voltage(kV)	4		
额定扭矩/Torque Tightening(N·m/Lb·in)	M2.5: 0.4/3.54		
导线范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.2~2.5/28~12		
间距/Pitch(mm)/线数范围/Poles	5.08/N=02~24P		
剥线长度/Stripping length(mm)	7~8		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS标准/Conform to RoHS	Yes		

宁波高松电子有限公司  
NINGBO DEGSON ELECTRICAL CO., LTD

