



标注公差/General Tolerances(mm)		0.1/10
0	>3	~
~	>6	~
3	6	~
~	10	~
~	18	~
~	30	~
~	50	~
~	80	~
~	120	~
~	180	~
~	250	~
~	315	~
~	400	~
~	500	~
~	>500	~
±0.12	±0.18	±0.20
±0.22	±0.26	±0.31
±0.37	±0.57	±0.80
±1.03	±1.05	±1.15
±1.60	±2.20	±2.50
±2		

IEC60947-7-1 UL1059
 CE DVE c PA US
 630V 32A 300V 30A
 0.2-4mm² 24-10 AWG

PCDK4

5	Screw2	Copper alloy	M3/Ni Plated
4	Screw1	Copper alloy	M3/Ni Plated
3	Current Carrier	Copper	Sn Plated
2	Cage	Copper alloy	M3/Ni Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
SURFACE: /			

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)/Current(A)	300/30	/	300/10
IEC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/污染等级/ Pollution Degree	III/3	/	/
额定电压/电流/Rated Voltage(V)/Current(A)	630/32	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6.0	/	/
螺丝扭矩/Torque Tightening(N·m/Lb·in)	M3, 0.5/4.43		
线在范围(硬线和软线)/Wire Range(rigid and flexible) (mm ² /AWG)	0.2~4.0/24~10		
可拆卸/Plitch(mm)	6.20		
剥线长度/Stripping length(mm)	7-8		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

REV	ECN	DESCRIPTION	DRAFT	DATE
1	2	2		
2	3	3		
3	4	4		

MATERIAL: /
 MAT NO.: /
 STATUS: /
 APPD: LiGL 2020.04.01 NAME: **DEGSON** 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD
 CHKD: MGEK 2020.04.01
 DRAFT: ZYH 2008.01.11 DRAWING NO.: PCDK4-C01
 TYPE: CUSTOMER DRAWING SCALE: 2:1 SHEET 1/1