



公差/General tolerances(mm)	
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.57
±0.80	±0.93
±1.05	±1.15
±1.60	±2.20
±2.50	
0.1/10	
±Z	

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	/	/	/
EC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	/	/
额定电压/电流/Rated Voltage(V)/Current(A)	/	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.2~6/24~10		
间距/Pitch(mm)	8.0		
剥线长度/Stripping length(mm)	12~13		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	/		
PANTONE / RAL	/		
SURFACE:	/		

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD: Li GL	2020.05.29
CHKD: Mao J	2020.05.29
DRT:Wang Y2	2020.05.29
NAME:	WS6-PE-01P-1C-00A(H)
DRAWING NO.:	WS6-PE-C01
TYPE:	CUSTOMER DRAWING
SCALE:	1:1
SHEET	1/1

DEGSON® 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

4	Grounding	Copper Alloy	Sn Plated
3	Current Carrier	Copper	Sn Plated
2	Spring	Stainless Steel	
1	Housing	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
1			

REV	ECN	DESCRIPTION	DRT	DATE