



公差/General Tolerances(mm)		公差/General Tolerances(mm)										公差/General Tolerances(mm)				
尺寸/Dimension	公差/Tolerance	0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/1.0
长度/Length	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±2.50	±2.50	0.1/1.0
宽度/Width	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±2.50	0.1/1.0
厚度/Thickness	±0.10	±0.12	±0.15	±0.20	±0.25	±0.30	±0.40	±0.50	±0.60	±0.80	±1.00	±1.20	±1.50	±2.00	±2.50	0.1/1.0

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing	PA66	UL94V-0
2	Spring	Stainless steel	
3	Current carrier	Copper	Sn Plated
4	Grounding	Copper alloy	Sn Plated

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
IEC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/污秽等级/Pollution Degree	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
额定冲击电压(kV)/Rate Impulse Voltage(kV)	8.0	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm² /AWG)	0.2~1.5/28~16	/	/
厚度/Pitch(mm)	4.0	/	/
剥线长度/Stripping length(mm)	9~10	/	/
使用温度范围/Operating Temperature(°C)	-40~+105	/	/
符合RoHS要求/Conform to RoHS	Yes	/	/
标准颜色编号/Standard color number:		/	/
PANTONE / RAL		/	/

MATERIAL:	SURFACE:
MAT NO.:	/
STATUS:	/
APPD:	Li GL 2020.05.30
CHKD:	Mco J 2020.05.30
DRAFT:	ZhengQG 2020.05.16
SIZE:	A4
TYPE:	CUSTOMER DRAWING
SCALE:	2:1
REV	TO
SHEET	1/1

DEGSON 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

NAME: **WS1.5-PE-01P-1C-00A(H)**

DRAWING NO.: WS1.5-PE-C01