



公差等级/General Tolerances(mm)		公差等级/General Tolerances(mm)										公差等级/General Tolerances(mm)																	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10																
~	~	~	~	~	~	~	~	~	~	~	~	~	±Z																
3	6	10	18	30	50	80	120	180	250	315	400	500	±Z																
±0.12		±0.18		±0.22		±0.26		±0.31		±0.37		±0.57		±0.80		±0.93		±1.05		±1.15		±1.60		±2.20		±2.50		±Z	

ITEM	NAME OF PART	MATERIAL	NOTES
6	Bridgeware	/	/
5	Current carrier 2	Copper	Sn Plated
4	Current carrier 1	Copper	Sn Plated
3	Spring	Stainless steel	/
2	Button	PA66-GF	UL94V-0
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				
4				

MATERIAL: /	SURFACE: /
MAT NO.: /	
STATUS: /	
APPD: LIQL 2020.04.01	NAME: DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD
CHKD: MoEK 2020.04.01	DSKK2.5-01P-1Y-50A(H)
DRAFT: YonH 2020.04.01	DRAWING NO.: DSKK2.5-C02
TYPE: CUSTOMER DRAWING	SCALE: 1:1
SIZE: A4	REV: D0-6
1/1	1/1

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/20	300/20	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	500/22	/	/
额定脉冲电压(kV)/Rate Impulse Voltage(kV)	6.0	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~2.5&4(50)/26~12		
间距/Pitch(mm)	5.20		
剥线长度/Stripping length(mm)	11~12		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		