






PCB LAYOUT







N=2



N=3



N=3



公差/General tolerances (mm)											D 0.1/10 ±2	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250		
~	~	~	~	~	~	~	~	~	~	~	~	~
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.50

N	Dim 'a'
4	8.42
5	8.42
6	13.5
7	13.5
8	18.58
9	18.58
10	23.66
11	23.66
12	28.74
13	28.74
14	33.82
15	33.82
16	38.9
17	38.9
18	43.98
19	43.98
20	49.06
21	49.06
22	54.14
23	54.14
24	59.22

Note:
The A&Z (H) in the name means: A (H) and Z (H).

2	Pin	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/18	/	300/10
IEC 标准/IEC Standard:			
过压类别/Ovenvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	250/15	320/15	630/15
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	4	4	4
间距/Pitch(mm)/线数范围/Poles	5.08/N=02~24P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

DEKSON MATERIAL: SURFACE/COLOR: MAT NO./REV: - / 00 MAT STATUS: 批量

NAME: 2EDGJ-5.08-XXP-1Y-00A&Z(H)

APPD: 兰春华	2022.09.06	NAME	
CHKD: 黄耀志	2022.09.06	DRAWING NO.	200029737
DRFT: 周锦雄	2022.09.06	TYPE	CUSTOMER DRAWING
00		DRAWING STATUS	已发布
REV	ECN	SCALE	2:1
	DESCRIPTION	SHEET	1/1
	DRFT	DATE	

Transfer or duplication of this document as well as the utilization of its contents without the written permission of DEKSON is prohibited. All rights reserved for patent. 复制或再行发布此文件以及未经许可擅自使用其内容均被禁止。所有权利均保留。 未经授权擅自复制或再行发布此文件以及未经许可擅自使用其内容均被禁止。所有权利均保留。