

총람

제품 장점



Interface module-DT010-00A(H)-30040000095

16 positions input output module,with indicator light,with screw connector and IDC stitching line,can access 16 positionsNPN/PNP signal,can be installed on DIN35 rail

제품 장점

Suitable for 16-point (20-bit interface) controller, Screw connection

제품 인증

기술 데이터

제품 도면

3D

□

Environmental data

Ambient temperature (operation)

-20 °C ... 70 °C

Ambient temperature (storage / transport)

-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations

IEC61810

Pollution level

3

Overvoltage category

III

Rated overvoltage

0.5kV

Flame retardant grade, in line with UL94

V0

Technical data

Installation location

Arbitrary

Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	16
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	20
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	18
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Dimension

length	65.5mm
width	57mm
Height	43mm

악세서리	
Accessories	
Wire harness	DX213-1S-500-00A(H)

비즈니스 데이터	
발주 번호	30040000095
포장 단위	1
MOQ	10
제품 무게 (포장 제외)	87