

총람

제품 장점



Interface module-DT007-00A(H)-30040000094

32 positions input output module, with indicator light, with screw connector and IDC stitching line, can access 32 positions NPN signal, can be installed on DIN35 rail

제품 장점

Suitable for 32-point (34/40-bit interface) controller, Screw connection

제품 인증

기술 데이터

제품 도면

3D

□

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
-----------------------	-----------

Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	32
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	40
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	34
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Dimension

length	111mm
width	57mm
Height	47mm

악세사리	
Accessories	
Wire harness	DX210-4S-500-00A(H)

비즈니스 데이터	
발주 번호	30040000094
포장 단위	1
MOQ	10
제품 무게 (포장 제외)	128