


## 총람

### 제품 장점



### DKE-009-MC-21020000129

Heavy-duty insert, Number of contacts: 9, Dimension: 1 module Spaces, Rated voltage : 50V, Rated current: 5A, Male insert, Crimping connector

### 제품 장점

- ☒ Crimping connection technology, applicable to a wide range of wire specifications ;
- ☒ Modular products, easy to assemble and maintain .

### 제품 인증



## 기술 데이터

### 제품 도면

### 3D

□

### Marking

|                |        |
|----------------|--------|
| classification | Insert |
| Series         | DM     |

### versions

|                     |                     |
|---------------------|---------------------|
| Connection method   | Crimping connection |
| Female/Male         | Male                |
| Dimension           | 1 module            |
| Number of positions | 9                   |
| PE Contacts         | No                  |

### Material characteristics

|                     |                             |
|---------------------|-----------------------------|
| Material (insert)   | Polycarbonate (PC)          |
| Materia (Contact)   | Copper alloy                |
| Surface (Contact)   | Silver plated/gold plated   |
| Flammability rating | V-0                         |
| color               | Grey/White (RAL 7032)       |
| RoHS                | Comply with RoHS exemptions |

Electrical parameters

|                                      |              |
|--------------------------------------|--------------|
| Rated current                        | 5A           |
|                                      | 50V          |
| Rated pulse voltage                  | 0.8KV        |
| Pollution level                      | 3            |
| On the basis of UL /CSARated current | 600V         |
| Insulation resistance                | ≥10000MΩ     |
| Contact resistance                   | ≤3mΩ         |
| Temperature range                    | -40℃~+125℃   |
| working life-mating cycles           | ≥500 time    |
| Conductor cross sections (mm²)       | 0.09-0.82mm² |
| Conductor cross sections(AWG)        | 28-18AWG     |

Standards

|                            |                           |
|----------------------------|---------------------------|
| Connection meets standards | DIN EN 60664 DIN EN 61984 |
|----------------------------|---------------------------|

악세사리

Accessories

|                            |   |
|----------------------------|---|
| Crimping tool Removal tool | / |
|----------------------------|---|

|               |             |
|---------------|-------------|
| 비즈니스 데이터      |             |
| 발주 번호         | 21020000129 |
| 포장 단위         | 100         |
| MOQ           | 5           |
| 제품 무게 (포장 제외) | 25.63       |