


총람

제품 장점



DMK-004-MC-21020000082

Heavy-duty insert, Number of contacts: 4, Dimension: 1 module Spaces, Rated voltage : 830V, Rated current: 40A, Male insert, Crimping connector

제품 장점

- ☒ Crimping connection technology, applicable to a wide range of wire specifications ;
- ☒ Modular products, easy to assemble and maintain .

제품 인증



기술 데이터

제품 도면

3D

□

Marking

classification	Insert
Series	DM

versions

Connection method	Crimping connection
Female/Male	Male
Dimension	1 module
Number of positions	4
PE Contacts	No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	40A
	830V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3/3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Conductor cross sections (mm²)	1.5-6mm²
Conductor cross sections(AWG)	16-10AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

악세서리

Accessories

Crimping tool Removal tool	/
----------------------------	---

비즈니스 데이터	
발주 번호	21020000082
포장 단위	100
MOQ	5
제품 무게 (포장 제외)	9