


총람

제품 장점



D2MK-001-M(25-40mm²)-21020000253

Heavy-duty insert, Number of contacts: 1, Dimension: 2 module Spaces, Rated voltage : 1000V, Rated current: 200A, Male insert, axial Screw connector

제품 장점

- ☒ Axial Screw connection technology, applicable to a wide range of wire specifications;
- ☒ Less materials, easy to manage;
- ☒ Modular products, easy to assemble and maintain .

제품 인증



기술 데이터

제품 도면

3D

□

Marking

classification	Insert
Series	DM

versions

Connection method	Axial screw connection
Female/Male	Male
Dimension	2 module
Number of positions	1
PE Contacts	No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	200A
	1000V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.2mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	16mm
Rated torque	8N.m(25/35mm²) 9N.m(50mm²) 10N.m(70mm²)
Conductor cross sections (mm²)	25-40mm²
Conductor cross sections(AWG)	4-1AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

악세사리

Accessories

SW 5 internal hexagonal wrench

/

비즈니스 데이터

발주 번호	21020000253
포장 단위	100
MOQ	5
제품 무게 (포장 제외)	62.7