


총람

제품 장점



DK-4/8-F-21020000067

Heavy-duty insert, Number of contacts: 4/8+PE, Dimension: 24B, Rated voltage : 400/400V, Rated current: 80/16A, Female insert, Screw connector

제품 장점

- ☑ Screw connection technology, applicable to a wide range of wire specifications;
- ☑ No need special tools, easy to operate;
- ☑ Less materials, easy to manage;
- ☑ With grounding protection.

제품 인증



기술 데이터

제품 도면

3D



Marking

classification	Insert
Series	DK

versions

Connection method	Screw connection
Female/Male	Female
Dimension	24B
Number of positions	4/8
PE Contacts	Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	400/400V
Rated pulse voltage	6/6KV
Pollution level	3
On the basis of UL /CSARated current	600/600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3/3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	6-9mm
Rated torque	1.2N.m(1.5mm²) 2N.m(2.5mm²) 3N.m(4/6/10/16mm²) 0.5N.m
Conductor cross sections (mm²)	1.5-16mm²/1.0-2.5mm²
Conductor cross sections(AWG)	16-6/20-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

악세사리

Accessories

Screwdriver

/

비즈니스 데이터

발주 번호	21020000067
포장 단위	100
MOQ	5
제품 무게 (포장 제외)	141