


총람

제품 장점



DA-010-MC-21020000156

Heavy-duty insert, Number of contacts: 10+PE, Dimension: 10A, Rated voltage : 250V, Rated current: 16A, Male insert, Crimping connector

제품 장점

- ☑Crimping connection technology, high wiring efficiency
- ☑Suitable for vibration occasions;
- ☑The wiring harness can be pre-installed;
- ☑Choose contacts with different wire diameters and coatings;
- ☑High-density pins, saving installation space;
- ☑With grounding protection.

제품 인증



기술 데이터

제품 도면

3D



Marking

classification	Insert
Series	DA

versions

Connection method	Crimping connection
Female/Male	Male
Dimension	10A
Number of positions	10

PE Contacts	Yes
-------------	-----

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	16A
	250V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	7.5mm
Conductor cross sections (mm²)	0.14-4.0mm²
Conductor cross sections(AWG)	26-12AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accessories

Crimping tool|Removal tool

/

비즈니스 데이터	
발주 번호	21020000156
포장 단위	100
MOQ	5
제품 무게 (포장 제외)	30