

총람

제품 장점



DA-003-F-21020000001

Heavy-duty insert, Number of contacts: 3+PE, Dimension: 3A, Rated voltage : 400/230V, Rated current: 10A, Female insert, Screw connector

제품 장점

- ☒ Screw connection technology, applicable to a wide range of wire specifications;
- ☒ No need special tools, easy to operate;
- ☒ Less materials, easy to manage;
- ☒ With grounding protection.

제품 인증



기술 데이터

제품 도면

3D

□

Marking

classification	Insert
Series	DA

versions

Connection method	Screw connection
Female/Male	Female
Dimension	3A
Number of positions	3
PE Contacts	Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	10A
	400/230V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	4.5mm
Rated torque	0.25N.m
Conductor cross sections (mm²)	0.75-1.5mm²
Conductor cross sections(AWG)	18-16AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

악세사리

Accessories

Screwdriver

/

비즈니스 데이터

발주 번호	21020000001
포장 단위	100
MOQ	5
제품 무게 (포장 제외)	12.78