


총람

제품 장점



WS35-11030000266

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 1000 V, Rated current: 125 A, Number of connectors: 2, Number of potentials: 1, Cross section: 2.5 mm² - 35 mm², AWG: 14 - 2, Width: 16 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

제품 장점

- ☑ spring-cage connection technology, good anti-vibration performance;
- ☑ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑ Unique plug-in bridge, high circuit connection efficiency;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

제품 인증



기술 데이터

제품 도면

3D

□

Wiring data

Strip length	25mm
Conductor cross section solid	0.2~35mm ²
Conductor cross section flexible	0.2~35mm ²
Conductor cross section solid AWG	14~2

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

UL Electrical parameters	
Rated current	115A
IEC Electrical parameters	
Rated voltage (III / 3)	1000V
Rated current (III / 3)	125A
Rated surge voltage	8KV
Environmental protection	
REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances
Dimension	
NS 35/7,5 Height	59.2mm
NS 35/15 Height	66.7mm
length	99.9mm
width	16mm
Height	58.4mm
Overview	
Connection type	Pull back spring connection
Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

악세사리

Marker

Top marker	ZT12
Side marker	/
Marker support	DTH5-25×5 / DTH5-25×12
Warning cover	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×5.5
Adjacent jumper (2P)	/
Alternate jumper (2P)	/
Staggered jumper (2P)	/
End cover	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

Accessories

End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

비즈니스 데이터

발주 번호	11030000266
포장 단위	20
MOQ	20

제품 무게 (포장 제외)	78.61
---------------	-------