


총람

제품 장점



WS10-TW-PE-11030000026

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Number of connectors: 3, Number of potentials: 1, Cross section: 0.2 mm² - 10 mm², AWG: 24 - 8, Width: 10 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

제품 장점

- ☑spring-cage connection technology, good anti-vibration performance;
- ☑Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑Grounding structure, protection circuit;
- ☑Can be matched with marker strips to avoid incorrect insertion of wires.

제품 인증



기술 데이터

제품 도면

3D

□

Wiring data

Strip length	13~14mm
Conductor cross section solid	0.2~10mm ²
Conductor cross section flexible	0.2~10mm ²
Conductor cross section solid AWG	24~8

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	42.5mm
End plate width	2.5mm
NS 35/15 Height	50mm
width	10mm
Height	42mm

Overview

Connection type	Pull back spring connection
Number of rows	1
number of connections	3
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

악세사리

Marker

Top marker	ZB10 / WB5
Side marker	DEK6
Marker support	DTH5-25×5 / DTH5-25×12
Warning cover	EEA10

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.8×5.5
Adjacent jumper (2P)	/
Alternate jumper (2P)	/
Staggered jumper (2P)	/
End cover	D-WS10-TW

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

Accessories

End cover	D-WS10-TW
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

비즈니스 데이터

발주 번호	11030000026
포장 단위	20
MOQ	20
제품 무게 (포장 제외)	37.504