

종람

#### 제품 장점



# WS1.5-DB-11030000035

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 800 V, Rated current: 17.5 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, AWG: 28 - 16, Width: 5 mm, Color: gray, Mounting type: Panel installation

### 제품 장점

☑Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;

☑Panel installation, no need to install on the guide rail;

☑Can be matched with marker strips to avoid incorrect insertion of wires.

제품 인증







## 기술 데이터

제품 도면

3D

## Wiring data

Strip length	8~9mm
Conductor cross section solid	0.2~1.5mm²
Conductor cross section flexible	0.2~1.5mm²
Conductor cross section solid AWG	28~16

#### **Environmental conditions**

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

EC Electrical parameters	
Rated voltage (III / 3)	800V
Rated current (III / 3)	17.5A
Rated surge voltage	8KV
Environmental protection	
REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances
Dimension	
End plate width	2.5mm
length	25mm
width	5mm
Height	17mm
Overview	
Connection type	Pull back spring connection
Number of rows	1
number of connections	2
Open-end side panels	Yes

악세사리		
Marker		
Top marker	1	

PΑ

V0

Insulation Materials

Flame retardant grade, in line with UL 94  $\,$ 

Top marker	I
Side marker	DEK5
Marker support	1

Warning cover	1
ccessories	
Slotted screwdriver size (Blade thickness x Width)	0.4×2.5
Adjacent jumper (2P)	1
Alternate jumper (2P)	1
Staggered jumper (2P)	/
End cover	D-WS1.5-DB
stallation	
DIN rail mounting adapter	WHH-WS1.5-DB
End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)
arking & Installation	
Marking strip	DEK5
ccessories	
End cover	D-WS1.5-DB
Rail adapter	WHH-WS1.5-DB

비즈니스 데이터	
발주 번호	11030000035
포장 단위	100
MOQ	100
제품 무계 (포장 제외)	1.614