

종람

제품 장점



PC4-HE-11010000076

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 800 V, Rated current: 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 4mm², AWG: 24 - 10, Width: 8.2 mm, Fuse type: Glass/ceramic/..., Fuse type: G / 5 x 20, Color: black, Mounting type: NS 35/7.5, NS 35/15.

제품 장점

☑Fuse terminal blocks;

☑Screw connection technology, reliable connection;

☑Copper alloy material, good corrosion resistance;

☑Can be matched with marker strips to avoid incorrect insertion of wires.

제품 인증





기술 데이터

제품 도면

3D

Wiring data

Screw type	Slotted screw
2 flexible conductors with a TWIN ferrule	0.5-1.5mm²
Strip length	8~9mm
Conductor cross section solid	0.2~4mm²
Conductor cross section flexible	0.2~4mm²
Conductor cross section solid AWG	24~10
screw thread	M3

Tightening torque	0.5N.m
Environmental conditions	
Ambient temperature (operation) -40 °C ~ 105 °C (depending on derating curve)	
Relative humidity (storage/transport)	25%~75%
EC Electrical parameters	
Rated voltage (III / 3)	800V
Rated current (III / 3)	6.3A
Rated surge voltage	8KV
Environmental protection	
REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances
Dimension	
NS 35/7,5 Height	57.4mm
NS 35/15 Height	64.9mm
length	72.89mm
width	8.2mm
Height	49.6mm
Overview	
Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	VO
fuse	G/5 x 20

Fuse type Glass/ceramic/	
--------------------------	--

악세사리

Slotted screwdriver size (Blade thickness x Width)	0.6×3.5
Fixed bridge	1
Insertion bridge	EB2-8 / EB3-8 / EB10-8
End cover	1
Separating disk	1
Partition plate	1

Marker

Top marker	1
Marker	ZB8
Marker support	1

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB8
Marker cards	DBE-1

Accessories

End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

비즈니스 데이터

발주 번호	11010000076
포장 단위	45
MOQ	45
제품 무계 (포장 제외)	18.145