

종람

제품 장점



DC4-HE-11020000045

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 500 V, Rated current: 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.5 mm^2 - 4mm^2 , AWG: 22 - 10, Width: 8 mm, Fuse type: Glass/ceramic/..., Fuse type: $G / 5 \times 20$, Color: black, Mounting type: NS 35/7.5, NS 35/15.

제품 장점

☑Fuse terminal blocks;

☑Steel screw connection technology, reliable connection;

☑The box has a baffle to prevent mis-insertion;

☑Can be matched with marker strips to avoid incorrect insertion of wires.

제품 인증



기술 데이터

제품 도면

3D

Wiring data

| Screw type | Slotted screw |
|---|---------------|
| 2 flexible conductors with a TWIN ferrule | 0.5-1.5mm² |
| Conductor cross section flexible (ferrule with plastic sleeve) | 0.5-2.5mm² |
| Conductor cross section flexible (ferrule without plastic sleeve) | 0.5-4mm² |
| Strip length | 8~9mm |
| Conductor cross section solid | 0.5~6mm² |

| Conductor cross section flexible | 0.5~4mm² |
|-----------------------------------|----------|
| Conductor cross section solid AWG | 22~10 |
| screw thread | M3 |
| Tightening torque | 0.6N.m |

Environmental conditions

| Ambient temperature (operation) | -40 °C ~ 105 °C (depending on derating curve) |
|---------------------------------------|---|
| Relative humidity (storage/transport) | 25%~75% |

IEC Electrical parameters

| Rated voltage (III / 3) | 500V |
|-------------------------|------|
| Rated current (III / 3) | 6.3A |
| Rated surge voltage | 6KV |

Environmental protection

| REACh SVHC | Lead 7439-92-1 |
|------------|---------------------------------|
| RoHS | No excessive harmful substances |

Dimension

| NS 35/7,5 Height | 48mm |
|------------------|--------|
| End plate width | 1.5mm |
| NS 35/15 Height | 55.5mm |
| length | 58mm |
| width | 8mm |
| Height | 46.5mm |

Overview

| Connection method | screw connection |
|-----------------------|------------------|
| Number of rows | 1 |
| number of connections | 2 |

| Open-end side panels | Yes |
|---|----------------|
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |
| fuse | G/5 x 20 |
| Fuse type | Glass/ceramic/ |

악세사리

| M | 2 | r | Ŀ | ۵ | 1 |
|---|---|---|---|---|---|

| Top marker | 1 |
|----------------|-----|
| Side marker | ZB8 |
| Marker support | 1 |

Accessories

| Slotted screwdriver size (Blade thickness x Width) | 0.6×3.5 |
|--|---------------------------|
| Bridge | EBC2-8 / EBC3-8 / EBC10-8 |
| End cover | D-DC4-HE |
| Partition plate | 1 |

Installation

| End clamp | E-WS N / E-PC-1100A |
|-------------------------------|--|
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5 & NS35/15 |

Marking & Installation

| Marking strip | ZB8 |
|---------------|-------|
| Marker cards | DBE-1 |

Accessories

| | End cover | D-DC4-HE |
|--|-----------|----------|
|--|-----------|----------|

| End clamp | E-WS |
|-----------|----------------------|
| DIN rail | NS35/7.5-1000-00A(H) |

| 비즈니스 데이터 | |
|---------------|-------------|
| 발주 번호 | 11020000045 |
| 포장 단위 | 50 |
| MOQ | 50 |
| 제품 무계 (포장 제외) | 11.472 |