


총람

제품 장점



DS2.5-TW-11040000035

Push-in Din-Rail TB, connector method: Push-in connector, Rated voltage : 800 V, Rated current : 24 A, Number of connectors: 3, Number of potentials: 1, Cross section: 0.2 mm² - 4 mm², AWG: 26 - 12, Width: 5.2 mm, Color: gray, Mounting type: NS35/7.5, NS35/15

제품 장점

- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With orange wire button, one word or cross screwdriver can release wire.
- ☑ Equipped with dual-channel bridge wells, circuit connection testing is more flexible.
- ☑ Unique plug-in bridge, high circuit connection efficiency.
- ☑ Optional marker to avoid wire mis-inserting.
- ☑ Equipped with test holes for easy testing of the circuit.

제품 인증



기술 데이터

제품 도면

3D

□

Wiring data

| | |
|-----------------------------------|---------|
| Strip length | 10~12mm |
| Conductor cross section solid AWG | 26~12 |

Environmental conditions

| | |
|---------------------------------------|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75% |

IEC Electrical parameters

| | |
|-------------------------|------|
| Rated voltage (III / 3) | 800V |
| Rated current (III / 3) | 24A |
| Rated surge voltage | 8KV |

Environmental protection

| | |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

Dimension

| | |
|------------------|--------|
| NS 35/7,5 Height | 36.8mm |
| End plate width | 2.2mm |
| NS 35/15 Height | 44.3mm |
| length | 60.5mm |
| width | 5.2mm |

Overview

| | |
|---|--------------------|
| Connection type | In line connection |
| Number of rows | 1 |
| number of connections | 3 |
| Open-end side panels | Yes |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

악세사리

Marker

| | |
|----------------|------------------------|
| Top marker | ZB5 / ZS5 |
| Side marker | ZSF5 |
| Marker support | DTH5-25x5 / DTH5-25x12 |

Accessories

| | |
|---|------------|
| Slotted screwdriver size (Blade thickness x Width) mm | 0.6x3.5 |
| Bridge | DFBXX-5.2 |
| End cover | D-DS2.5-TW |

Installation

| | |
|-------------------------------|---------------------------------------|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5-1000-00A(H) |

비즈니스 데이터

| | |
|---------------|-------------|
| 발주 번호 | 11040000035 |
| 포장 단위 | 100 |
| MOQ | 100 |
| 제품 무게 (포장 제외) | 7.578 |