

## 총람

### 제품 장점



**FT-M12D-04M-M12D-04F-Q-0200-20030002033**

M12D-T distributor(soldering), Input terminal: Male, Output terminal: Female

### 제품 장점

- ☒ Single wire input, Multi wire output
- ☒ Cost saving and convenient installation
- ☒ Protection level: IP67/68
- ☒ Widely used in industrial automation, rail transit and other industries

### 제품 인증

**RoHS REACH**

## 기술 데이터

### 제품 도면

### 3D

□

### Environmental conditions

Ambient temperature

-25℃...85℃

IP class

IP67

### General parameters

Rated current

4A

250V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

D-Code

|                             |       |
|-----------------------------|-------|
| Overvoltage level           | II    |
| Pollution level             | 3     |
| Insertion and pullout cycle | ≥ 100 |

Material

|                                        |                           |
|----------------------------------------|---------------------------|
| Flammability rating ,in line with UL97 | HB                        |
| Contact material                       | CuZn                      |
| Material contact surface               | Au                        |
| Contact carrier material               | PU                        |
| Fixture body material                  | TPU                       |
| Coil material                          | Zinc alloy, nickel plated |
| Sealing material                       | Silicon                   |

악세사리

비즈니스 데이터

|               |             |
|---------------|-------------|
| 발주 번호         | 20030002033 |
| 포장 단위         | /           |
| MOQ           | 100         |
| 제품 무게 (포장 제외) | /           |