

총람

제품 장점



SD-M12B-05P-FF-SH8001-20030001182

Sensor/Actuator Female socket, M12, Coding B, Front panel installation/PG9
Thread mounted, Soldering cup

제품 장점

- ☒ Sealing optimization, protection level up to IP68
- ☒ Meet the harsh environment
- ☒ Suitable for various occasions connection technology
- ☒ Compatible with the international and domestic same series products

제품 인증



RoHS

REACH



기술 데이터

제품 도면

3D

□

Environmental conditions

Ambient temperature

-40°C...105°C

IP class

IP68

General parameters

Rated current

4A

60V

Number of potentials

5

Insulation resistance

≥ 100 MΩ

Error-proof coding

B-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Installation in front of the board

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

악세사리

Accessories

Sealing cap	CAP-M12-MP-8002
-------------	-----------------

비즈니스 데이터

발주 번호	20030001182
포장 단위	/
MOQ	100
제품 무게 (포장 제외)	/

