


총람

제품 장점



SD-M12B-05P-FF-SH8B50-20030001185

Sensor/Actuator Female socket, M12, Coding B, Front panel installation/M16*1.5 Thread mounted, With 0.5m litz wires

제품 장점

- ☒ Sealing optimization, protection level up to IP68
- ☒ Meet the harsh environment
- ☒ Suitable for various occasions connection technology
- ☒ Compatible with the international and domestic same series products

제품 인증



RoHS

REACH



기술 데이터

제품 도면

3D



Environmental conditions

Ambient temperature	-25℃...80℃
IP class	IP68

General parameters

Rated current	4A
	60V
Number of potentials	5
Insulation resistance	≥ 100 MΩ
Error-proof coding	B-Code

Overvoltage level	II
Pollution level	3
Connection method	Single wire
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Installation in front of the board

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

Cable

UL AWM form	UL1061
Cross section	0.34mm²
AWG signal wire	22AWG
Wire structure Signal wire	17/0.16mm²
Core diameter (including insulation layer)	1.30±0.05mm
Wire color	1 Brown 2 White 3 Blue 4 Black 5 Gray
Thickness, insulation	0.203mm
Conductor insulation material	PVC
Conductor material	Tinned copper

Insulation resistance	≥ 20 MΩ
Conductor resistance	Maximum 94.2Ω/km (at 20 °C)
Nominal cable voltage	300V
Cable test voltage	2000V
Dimension	
Cable length	0.5m

악세서리	
Accessories	
Sealing cap	CAP-M12-MP-8003

비즈니스 데이터	
발주 번호	20030001185
포장 단위	/
MOQ	100
제품 무게 (포장 제외)	/