

총람

제품 장점



DG49-A-12050000001

Transfer barrier terminal blocks, Rated current: 20A. Rated voltage (UL) : 300V, Cross section: 22~12AWG, pitch: 9.5mm, Color: black, Contact surface: Tin

제품 장점

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Panel mounting for electrical transfer between two devices in a small space

제품 인증



기술 데이터

제품 도면

3D

□

Connection capacity

| | |
|--------|----------|
| AWG | 22~12AWG |
| Torque | 0.8N.m |

Electrical parameters UL

| | |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (C) | 150V |
| Rated voltage (D) | 300V |
| Rated current (B) | 20A |
| Rated current (D) | 10A |

| | |
|-------------------|-----|
| Rated current (C) | 20A |
|-------------------|-----|

Electrical parameters IEC

| | |
|---------------|------|
| Rated current | 600V |
| | 32A |

Item properties

| | |
|----------------------|-------------------------------|
| Type of installation | panel |
| Pin arrangement | Double-row in a straight line |
| Connection method | Screw connection |
| Screwdriver | slotted-phillips screwdriver |
| screw thread | M3.5 |
| Pitch | 9.5mm |
| Number of potentials | 2 |
| Pluggable or not | no |
| Number of rows | 1 |

Material data

| | |
|-----------------------------|---------------------------|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact point metal surface | tin-plated |
| Insulation Materials | PC |
| Insulating material group | IIIa |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|--------------------|--------|
| Test Specification | UL1059 |
|--------------------|--------|

Environmental data

| | |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~125℃ |
|---------------------------------|-----------|

| | |
|-------------|-----|
| 악세사리 | |
| Accessories | |
| Bridge | K55 |

| | |
|---------------|-------------|
| 비즈니스 데이터 | |
| 발주 번호 | 12050000001 |
| 포장 단위 | 475 |
| MOQ | / |
| 제품 무게 (포장 제외) | 7.9 |