

총람

제품 장점



DG35C-B-12020000130

Single-layer PCB barrier terminal blocks, Rated current: 20A. Rated voltage (UL) : 300V, Cross section: 22~12AWG, pitch: 8.25mm, Color: black, Contact surface: Tin

제품 장점

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Solder plate mounting for electrical connection of the device to the PCB

제품 인증



기술 데이터

제품 도면

3D

□

Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

Connection capacity

AWG	22~12AWG
Torque	0.5N.m

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A

Rated current (D)	10A
-------------------	-----

Electrical parameters IEC

Rated current	1000V
	32A

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3
Pitch	8.25mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

악세사리

Accessories

비즈니스 데이터	
발주 번호	12020000130
포장 단위	100
MOQ	/
제품 무게 (포장 제외)	4.7