

## 총람

### 제품 장점



### DG32-A-12010000207

Single-layer PCB barrier terminal blocks, Rated current: 120A. Rated voltage (UL) : 600V, Cross section: 20~2AWG, pitch: 28mm, Color: black, Contact surface: Tin

### 제품 장점

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ High current electrical connections at the power end can be met

### 제품 인증



## 기술 데이터

### 제품 도면

#### 3D

□

### Connection capacity

AWG	20~2AWG
Torque	2.5N.m

### Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	120A
Rated current (D)	5A

Rated current (C)	120A
-------------------	------

Item properties

Type of installation	panel
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M6
Pitch	28mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40℃~125℃
---------------------------------	-----------

악세사리

Accessories

비즈니스 데이터	
발주 번호	12010000207
포장 단위	20
MOQ	/
제품 무게 (포장 제외)	102.1