


총람

제품 장점



DGK12-003-13030000005

Building electronic housing ,length :161.6mm,DIN rail housing ,Can be used in distribution box comply with DIN 43880 standard , Upper housing with vent , IP class:IP20.

제품 장점

- ☒ Modern design
- ☒ flexible PCB connection
- ☒ high-efficiency DIN rail connector is optional
- ☒ Support Wall-mounted installation and distribution power box installation in accordance with DIN 43880 standards

제품 인증

기술 데이터

제품 도면

3D

□

Dimensions

width	161.6mm
length	89.7mm
Height	60.7mm
Depth from top edge of DIN rail	54.7mm

PCB data

Number of PCB holders	27 (Upper cover 18+Base 9)
PCB thickness	1.8mm
Installation location	Vertical &horizontal(DIN rail)
PCBType of installation	Latching

Item properties	
IP class	IP20
Connection levels	1(Both sides)
with ventilation openings	Yes
Maximum connection	96 (pitch : 2.5 mm);54 (pitch : 5 mm),36 (pitch : 7.5 mm)
Material data	
color	Upper housing: light gray bottom housing: black
Material	PC
Flammability rating	V2
Environmental data	
Ambient temperature (assembly)	-5℃ ~ +100℃
Ambient temperature (operation)	-40℃ ~ +110℃
Ambient temperature (storage / transport)	-40℃ ~ +70℃

악세사리
Accessories

비즈니스 데이터	
발주 번호	13030000005
포장 단위	35
MOQ	35
제품 무게 (포장 제외)	111.4