

총람

제품 장점



DGK12-002-13030000004

Building electronic housing ,length :71.6mm,DIN rail housing ,Can be used in distribution box comply with DIN 43880 standard , Upper housing with vent , IP class:IP20.

제품 장점

- ☑Modern design
- ☑flexible PCB connection
- ☑high-efficiency DIN rail connector is optional
- ☑Support Wall-mounted installation and distribution power box installation in accordance with DIN 43880 standards

제품 인증

기술 데이터

제품 도면

3D

□

Dimensions

| | |
|---------------------------------|--------|
| width | 71.6mm |
| length | 89.7mm |
| Height | 60.7mm |
| Depth from top edge of DIN rail | 54.7mm |

PCB data

| | |
|-------------------------|--------------------------------|
| Number of PCB holders | 17 (Upper cover 8+Base 9) |
| PCB thickness | 1.8mm |
| Installation location | Vertical &horizontal(DIN rail) |
| PCBType of installation | Latching |

| Item properties | |
|---|---|
| IP class | IP20 |
| Connection levels | 1(Both sides) |
| with ventilation openings | Yes |
| Maximum connection | 44 (pitch : 2.5 mm);24 (pitch : 5 mm),16 (pitch : 7.5 mm) |
| Material data | |
| color | Upper housing: light gray bottom housing: black |
| Material | PC |
| Flammability rating | V2 |
| Environmental data | |
| Ambient temperature (assembly) | -5℃ ~ +100℃ |
| Ambient temperature (operation) | -40℃ ~ +110℃ |
| Ambient temperature (storage / transport) | -40℃ ~ +70℃ |

| 악세사리 | |
|-------------|--|
| Accessories | |
| | |

| | |
|---------------|-------------|
| 비즈니스 데이터 | |
| 발주 번호 | 13030000004 |
| 포장 단위 | 84 |
| MOQ | 84 |
| 제품 무게 (포장 제외) | 59.5 |