

총람

제품 장점



MIL cable-DX211-1S-500-00A(H)-23040000012

MIL cable,connector1:IDC/MIL female connector (1×34 Core,90° output) ,connector2:IDC/MIL female connector (1×40 Core,90° output)

제품 장점

- ☒ The cable is soft and has good bending resistance
- ☒ Prefabricated connector, beautiful appearance
- ☒ Provide single-ended and double-ended cables
- ☒ Suitable for KEYENCE KV series PLC
- ☒ Save wiring time, and can achieve fast wiring with the company's interface module

제품 인증

기술 데이터

제품 도면

3D

□

Environmental data

Ambient temperature (operation)	-20 °C ... 80 °C
Ambient temperature (storage / transport)	-20 °C ... 80 °C

Standards/Regulations

Flame retardant	ULVW-1
Oil resistance	Oil resistant
Gasoline resistance	≤246Ω/KM
Connection meets standards	UL758

Technical data

Maximum allowable working voltage	30VDC
-----------------------------------	-------

Maximum current carrying capacity of each path	0.7A
cable length	0.5米
Cable outer diameter	7.6mm
Single strand, cross-sectional area	0.08mm²
Single strand, cross section (AWG)	28

Connection data 1

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	34
spacing	2.54mm
Exit angle	90°

Connection data 2

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	40
Exit angle	90°
spacing	2.54mm

Overview

Single wire, number of twisted wires	40
Single stranded wire, material	Tinned copper
shield	Yes
Outer sheath, material	PVC

Outer sheath,color	black
--------------------	-------

약세사리

비즈니스 데이터	
발주 번호	23040000012
포장 단위	1
MOQ	10
제품 무게 (포장 제외)	50