

## 총람

### 제품 장점



## TSCF4-10070000087

Transformer terminal blocks, Rated current: 10A. Rated voltage  
(III/2) : 250V, Color: Orange, Contact surface : Tin

### 제품 장점

- ☒ Screw connection technology, safe and reliable
- ☒ Built-in fuse for over-current protection
- ☒ Rail installation method, suitable for transformer wiring

### 제품 인증



## 기술 데이터

### 제품 도면

#### 3D

□

### Connection capacity

Conductor cross section solid	0.2~4mm <sup>2</sup>
Conductor cross section flexible	0.5~4.0mm <sup>2</sup>
AWG	30~10AWG
Torque	0.8N.m
Strip length	8mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	8A

### Electrical parameters IEC

Rated current	250V
	10A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3.5
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Accessories	
Coding strip	TZB4
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

비즈니스 데이터	
발주 번호	10070000087
포장 단위	400
MOQ	30
제품 무게 (포장 제외)	9.25