

총람

제품 장점



DG500-5.08-10040000216

PCB terminal blocks, Rated current: 18A, Rated voltage (III/2) 250V, Cross section: 1.0~2.5mm², pitch: 5.08mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

제품 장점

- ☒ Fixed screw connection technology, safe and reliable
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method to ensure a high degree of flexibility in device design

제품 인증



기술 데이터

제품 도면

3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid	1.0~2.5mm ²
Conductor cross section flexible	1.0~2.5mm ²
AWG	30~12AWG
Torque	0.5N.m
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	250V
Rated current	18A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5.08mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66

Insulating material group	I
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	UL1059/IEC60998
Environmental data	
Ambient temperature (operation)	-40℃~105℃

악세사리	
Accessories	
Coding strip	/
Bridge	DG019-5.0
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

비즈니스 데이터	
발주 번호	10040000216
포장 단위	500
MOQ	30
제품 무게 (포장 제외)	2.67