

총람

제품 장점



DG270-10.0-10060001644

PCB spring terminal blocks, Rated current: 76A. Rated voltage
(III/2) : 400V, pitch: 10.0mm, Color: green, Contact surface : Tin

제품 장점

- ☒ Cage clamp connection technology, fast wiring
- ☒ Universal installation method, suitable for various situations
- ☒ Rotatable operating handle, easy to operate

제품 인증



기술 데이터

제품 도면

3D

□

Electrical parameters IEC

Rated voltage	400V
Rated current(III/3)	400V
Rated current	76A
Rated current(III/2)	400V
Rated current(II/2)	800V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	0°
Pitch	10mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

악세사리

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

비즈니스 데이터	
발주 번호	10060001644
포장 단위	0
MOQ	30
제품 무게 (포장 제외)	10.15