


총람

제품 장점



DG262-7.5-10060001615

PCB spring terminal blocks, Rated current: 32A. Rated voltage
(III/2) : 320V, pitch: 7.5mm, Color: gray, Contact surface : Tin

제품 장점

- ☒ Universal installation method, suitable for various situations
- ☒ 45° connection can realize multi-row layout on PCB
- ☒ Different poles can be combined through the side lock

제품 인증



기술 데이터

제품 도면

3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~4mm²

Conductor cross section flexible

0.2~4.0mm²

AWG

28~12AWG

Strip length

9mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)	20A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated current(III/3)	500V
Rated current	32A
Rated current(III/2)	320V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	spring-cage connection
Pitch	7.5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated

Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC60947/UL 1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃

악세사리	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

비즈니스 데이터	
발주 번호	10060001615
포장 단위	570
MOQ	30
제품 무게 (포장 제외)	4.466