

총람

제품 장점



DG252-10080000069

Feed through terminal blocks, Rated current: 17.5A. Rated voltage
(III/2) : 450V, pitch: 10.0mm, Color: White, Contact surface : Zn

제품 장점

- ☒ Multiple wiring holes for current distribution
- ☒ Panel mounting, suitable for various situations
- ☒ Can realize horizontal wire-to-wire connection

제품 인증



기술 데이터

제품 도면

3D

□

Connection capacity

Conductor cross section solid	0.5~1.5mm ²
AWG	22~16AWG
Torque	0.8N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	10A

Electrical parameters IEC

Rated current	450V
	17.5A
Rated current(III/2)	450V
Rated power frequency voltage(1min)	2.5KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3.5
Pitch	10mm
Number of potentials	12
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	steel
Contact point metal surface	Galvanized
Insulation Materials	PA66
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

악세사리

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

비즈니스 데이터	
발주 번호	10080000069
포장 단위	100
MOQ	30
제품 무게 (포장 제외)	30