

총람

제품 장점



DG228-3.5-10060001647

PCB spring terminal blocks, Rated current: 24A. Rated voltage
(III/2) : 450V, pitch: 3.5mm, Color: transparent, Contact surface : Tin

제품 장점

- ☒ PUSH-IN connection technology, fast wiring
- ☒ Wire Connector for Mini Junction Box

제품 인증



기술 데이터

제품 도면

3D

□

Connection capacity

Conductor cross section solid	0.5~2.5mm ²
Conductor cross section flexible	0.5~2.5mm ²
AWG	22~14AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	600V
Rated current (B)	15A

Electrical parameters IEC

Rated current	450V
---------------	------

	24A
Rated current(III/2)	450V
Rated power frequency voltage(1min)	2.5KV

Item properties

Connection method	Push-in spring connection
Pitch	5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	steel
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~85℃
---------------------------------	----------

악세사리

Accessories

Coding strip	/
Bridge	/
Marking strip	/

Others	/
Tool	
Operating tool	/
Screwdriver	/

비즈니스 데이터	
발주 번호	10060001647
포장 단위	100
MOQ	30
제품 무게 (포장 제외)	1.83