

총람

제품 장점



DG224-8.0-10060001097

PCB spring terminal blocks, Rated current: 24A. Rated voltage
(III/2) : 450V, pitch: 8.0mm, Color: gray, Contact surface : Tin

제품 장점

- ☒ Cage clamp connection technology, fast wiring
- ☒ Can realize horizontal wire-to-wire connection

제품 인증



기술 데이터

제품 도면

3D

□

Connection capacity

Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
AWG	22~12AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	22A
Rated current (D)	10A

Electrical parameters IEC

Rated current	450V
	24A
Rated current(III/2)	450V
Rated power frequency voltage(1min)	2.5KV

Item properties

Connection method	Push-in spring connection
Pitch	8mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~85℃
---------------------------------	----------

악세사리

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

비즈니스 데이터	
발주 번호	10060001097
포장 단위	100
MOQ	30
제품 무게 (포장 제외)	4.5