


총람

제품 장점



DGBSC-SG01/4-10050000465

PCB spring terminal blocks, Rated current: 32A. Rated voltage
(III/2) : 450V, pitch: 5.6mm, Color: transparent, Contact surface : Tin

제품 장점

- ☒ Rotatable operating handle, easy to operate
- ☒ Suitable for field wiring, saving installation time

제품 인증



기술 데이터

제품 도면

3D

□

Connection capacity

Conductor cross section solid	0.2~4mm ²
Conductor cross section flexible	0.2~4.0mm ²
AWG	24~12AWG
Strip length	12mm

Electrical parameters UL

Rated voltage (B)	600V
-------------------	------

Electrical parameters IEC

Rated current	450V
	32A

Rated current(III/2)	450V
----------------------	------

Item properties

Connection method	Push-in spring connection
Pitch	5.6mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~85℃
---------------------------------	----------

악세사리

Accessories

Coding strip	/
Bridge	/
Marking strip	/

Others	/
Tool	
Operating tool	/
Screwdriver	/

비즈니스 데이터	
발주 번호	10050000465
포장 단위	100
MOQ	30
제품 무게 (포장 제외)	2.22