

## 총람

### 제품 장점



## DG2003-6.0-10060000597

PCB spring terminal blocks, Rated current: 17.5A. Rated voltage  
(III/2) : 200V, pitch: 6.0mm, Color: White, Contact surface : Tin

### 제품 장점

- ☒ PUSH-IN connection technology, fast wiring
- ☒ Suitable for SMT welding process
- ☒ Compact structure, saving installation space

### 제품 인증



## 기술 데이터

### 제품 도면

#### 3D

□

### Processing notes

Process

Reflow soldering/wave soldering/manual soldering

### Connection capacity

Conductor cross section solid

0.5~1.5mm<sup>2</sup>

Conductor cross section flexible

0.5~1.5mm<sup>2</sup>

AWG

20~16AWG

Strip length

10mm

### Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)

10A

#### Electrical parameters IEC

Rated voltage	200V
Rated current(III/3)	200V
Rated current	17.5A
Rated current(III/2)	200V
Rated current(II/2)	320V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

#### Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Push-in spring connection
Pitch	6mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC60947/UL1977
Environmental data	
Ambient temperature (operation)	-40℃~130℃

악세사리	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

비즈니스 데이터	
발주 번호	10060000597
포장 단위	900
MOQ	30
제품 무게 (포장 제외)	1