

총람

제품 장점



DG12HWP-1.2-10080000044

Feed through terminal blocks, Rated current: 41A. Rated voltage
(III/2) : 750V, pitch: 11.5mm, Color: natural, Contact surface : Zn

제품 장점

- ☒ Can realize horizontal wire-to-wire connection
- ☒ Panel mounting, suitable for various situations

제품 인증



기술 데이터

제품 도면

3D

□

Connection capacity

| | |
|----------------------------------|-------------------------|
| Conductor cross section solid | 0.75~6mm ² |
| Conductor cross section flexible | 0.75~6.0mm ² |
| AWG | 14~10AWG |
| Torque | 0.8N.m |
| Strip length | 9mm |

Electrical parameters UL

| | |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 20A |

| | |
|-------------------|-----|
| Rated current (D) | 10A |
|-------------------|-----|

Electrical parameters IEC

| | |
|-------------------------------------|------|
| Rated current | 750V |
| | 41A |
| Rated current(III/2) | 750V |
| Rated power frequency voltage(1min) | 3KV |

Item properties

| | |
|----------------------|---------------------|
| Type of installation | panel |
| Connection method | Screw connection |
| Screwdriver | Slotted screwdriver |
| screw thread | M3.5 |
| Pitch | 11.5mm |
| Number of potentials | 12 |
| Pluggable or not | no |

Material data

| | |
|-----------------------------|---------------------------|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | steel |
| Contact point metal surface | Galvanized |
| Insulation Materials | PA66 |
| Flammability rating | UL94V-2 |

Mechanical tests

| | |
|--------------------|-----------------|
| Test Specification | UL1059/IEC60998 |
|--------------------|-----------------|

Environmental data

| | |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~105℃ |
|---------------------------------|-----------|

| | |
|----------------|---|
| 악세사리 | |
| Accessories | |
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |
| Tool | |
| Operating tool | / |
| Screwdriver | / |

| | |
|---------------|-------------|
| 비즈니스 데이터 | |
| 발주 번호 | 10080000044 |
| 포장 단위 | 65 |
| MOQ | 30 |
| 제품 무게 (포장 제외) | 53.8 |