


총람

제품 장점



5EDGRC-10.16-10020000920

Pluggable terminal blocks, Rated current: 57A. Rated voltage
(III/3) : 600V, pitch: 10.16mm, Color: green, Contact surface : silver

제품 장점

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ The plug direction is parallel to the PCB

제품 인증



기술 데이터

제품 도면

3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	600V
Rated current (B)	52A
Rated current (D)	5A
Rated current (C)	52A

Electrical parameters IEC

Rated voltage	600V
Rated current(III/3)	600V
Rated current	57A
Rated surge voltage(III/3)	6KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Three rows in a straight line
Pitch	10.16mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	Silver plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	5EDG-PWI

비즈니스 데이터	
발주 번호	10020000920
포장 단위	220
MOQ	30
제품 무게 (포장 제외)	8.372