


총람

제품 장점



2EDGKR-7.62-10010002768

Pluggable terminal blocks, Rated current: 20A. Rated voltage
(III/2) : 400V, pitch: 7.62mm, Color: green, Contact surface : Tin

제품 장점

- ☒ Adapt to multi-type plugs, device design is highly flexible
- ☒ Keying parts can be installed
- ☒ Universal installation method, suitable for various situations

제품 인증



기술 데이터

제품 도면

3D

□

Connection capacity

Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
AWG	28~12AWG
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	630V
Rated current	20A
Rated current(III/2)	630V
Rated surge voltage(III/2)	6KV

Item properties

Connection direction	0°
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	7.62mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data	
Ambient temperature (operation)	-40℃~105℃

악세사리	
Tool	
Screwdriver	0.6x3.5, Slotted screwdriver
Operating tool	/
Accessories	
Coding strip	2EDG-PWP
Bridge	/
Marking strip	/
Others	/

비즈니스 데이터	
발주 번호	10010002768
포장 단위	200
MOQ	30
제품 무게 (포장 제외)	3.95