


## 총람

### 제품 장점



### 2EDGKQ-5.0-10010003750

Pluggable terminal blocks, Rated current: 10A. Rated voltage  
(III/2) : 250V, pitch: 5.0mm, Color: green, Contact surface : Tin

### 제품 장점

- ☒ Universal installation method, suitable for various situations
- ☒ Maximum contact force, low temperature rise
- ☒ Square connector, large wiring capacity

### 제품 인증



## 기술 데이터

### 제품 도면

#### 3D

□

### Connection capacity

Conductor cross section solid	0.2~1.5mm <sup>2</sup>
Conductor cross section flexible	0.2~1.5mm <sup>2</sup>
AWG	28~14AWG
Torque	0.5N.m
Strip length	7mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	10A

### Electrical parameters IEC

Rated voltage	250V
Rated current	10A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2.5KV

Item properties

Connection direction	0°
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3
Pitch	5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)

-40℃~105℃

#### 악세사리

##### Tool

Screwdriver

0.6x3.5, Slotted screwdriver

Operating tool

/

##### Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

/

#### 비즈니스 데이터

발주 번호

10010003750

포장 단위

280

MOQ

30

제품 무게 (포장 제외)

4.2