


## 총람

### 제품 장점



**15EDGVC-2.5-10030000638**

Pluggable terminal blocks, Rated current: 5A. Rated voltage  
( II / 2 ) : 250V, pitch: 2.5mm, Color: green, Contact surface : Tin

### 제품 장점

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ The plug direction is perpendicular to PCB

### 제품 인증



## 기술 데이터

### 제품 도면

#### 3D

□

### Processing notes

Process

Wave soldering/manual soldering

### Electrical parameters UL

Rated voltage (B)	150V
Rated voltage (C)	150V
Rated voltage (D)	150V
Rated current (B)	4A
Rated current (D)	4A
Rated current (C)	4A

### Electrical parameters IEC

Rated voltage	250V
Rated current	5A
Rated current(II/2)	250V
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	2.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	15EDG-PWI-2.5

비즈니스 데이터	
발주 번호	10030000638
포장 단위	500
MOQ	30
제품 무게 (포장 제외)	0.46