

총람

제품 장점



Bus IO-DF750-HT-200-11-1001A(H)-30050000227

Card IO housing, push-in structure, 16 aisle input and output module housing, with LED display, Gold finger connection is completely disconnected

제품 장점

- ☑ Hand-plugged, easy to assemble
- ☑ Internal bus through bottom 6 gold-plated terminals
- ☑ Equipped 16 channels functional module, LEDs per node
- ☑ Internal 2 gold-plated blade connectors for power cascading expansion
- ☑ Can be installed on DIN rail

제품 인증

기술 데이터

제품 도면

3D

□

Connection method (IO)

wiring

PUSH-IN wiring technology

Mechanical parameters

structure type	Compact terminal module housing with signal LED
Material	PC+PA66
installation	DIN35 rail
Side by side installation	Dovetail groove clamping
label	Laser screen printing
color	C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Connection method(IO)

Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Dimension

length	100mm
width	12mm (main module)
Height	66.8mm

악세사리

비즈니스 데이터

발주 번호	30050000227
포장 단위	200 SKT
MOQ	200 SKT
제품 무게 (포장 제외)	40g