

총람

제품 장점



Bus IO-DF750-HT-001-11-1001A(H)-30050000253

Card IO housing, push-in structure, Can be matched bring light RJ45 Connector, LED instruct

제품 장점

- ☒ Dual network port without light RJ45 interface
- ☒ 8-bit address interface
- ☒ Internal bus through bottom 6 gold-plated terminals
- ☒ Equipped 16 aisle Power Module, LEDs per node
- ☒ Internal 2 gold-plated blade connectors for power cascading expansion
- ☒ Can be installed on DIN rail

제품 인증

기술 데이터

제품 도면

3D

□

Connection method (IO)

wiring

PUSH-IN wiring technology

Mechanical parameters

structure type	Compact terminal module housing with signal LED
Material	PC+PA66
installation	DIN35 rail
Side by side installation	Dovetail groove clamping
label	Laser screen printing
color	C1 gray

Environmental data	
Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃
Connection method(IO)	
Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm ²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm
Dimension	
length	100mm
width	48mm
Height	69mm

악세사리

비즈니스 데이터	
발주 번호	30050000253
포장 단위	20 SKT
MOQ	20 SKT
제품 무게 (포장 제외)	122.5g