

총람

제품 장점



Relay base-DPKF08A-E3-00A(H)-30020000049

DPKFrelay base,used for2PDTrelay,screw connection

제품 장점

- ☒ Plug-in relay socket
- ☒ Safe isolation between coil and contacts
- ☒ 12A, 2PDTgrade
- ☒ Arc partition between adjacent columns
- ☒ Anti-touch cover at the top of the screw

제품 인증

기술 데이터

제품 도면

3D

□

Environmental data

| | |
|---|-------------------|
| Ambient temperature (storage/transport) | -40 °C ... +85 °C |
| Ambient temperature (operation) | -20 °C ... 50 °C |

Technical data

| | |
|-----------------------|------------|
| Rated voltage UN | 300V |
| Installation location | Arbitrary |
| Assembly instructions | DIN35 rail |

Connection data 1

| | |
|-------------------|------------------|
| Connection name | enter |
| Connection method | Screw connection |

| | |
|-------------------------------------|---------------------------|
| Stripping length | 7-8mm |
| screw thread | M3 |
| Cross section of flexible conductor | 0.5... 2.5mm ² |
| Connectable guide cross section AWG | 20-14AWG |

Connection data 2

| | |
|-------------------------------------|---------------------------|
| Connection name | Output |
| Stripping length | 7-8mm |
| Cross section of flexible conductor | 0.5... 2.5mm ² |
| Connectable guide cross section AWG | 20-14AWG |
| Connection method | Screw connection |

Dimension

| | |
|-------------------------|--------|
| length | 69.6mm |
| width | 25mm |
| Depth including bracket | 29.2mm |

악세사리

비즈니스 데이터

| | |
|---------------|-------------|
| 발주 번호 | 30020000049 |
| 포장 단위 | 20 SKT |
| MOQ | 20 SKT |
| 제품 무게 (포장 제외) | 62g |