

총람

제품 장점



Relay base-DSRC05A-F3-00A(H)-30020000063

DSRCrelay base,used for1PDTrelay,screw connection

제품 장점

- ☒ Plug-in relay socket
- ☒ Safe isolation between coil and contacts
- ☒ 10A, 1 PDT grade
- ☒ Arc partition between adjacent columns
- ☒ Strong and weak electricity separation

제품 인증

기술 데이터

제품 도면

3D

□

Environmental data

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage / transport)	-40~+65℃

Technical data

Rated voltage UN	300V
Rated current IN	10A
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
-----------------	-------

Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Dimension

length	80mm
width	16mm
Depth including bracket	61.5mm

악세사리

비즈니스 데이터

발주 번호	30020000063
포장 단위	
MOQ	
제품 무게 (포장 제외)	