

총람

제품 장점



DSW-A5K0005-30090000001

5 10/100Mbps BaseT port, IP30, Operating temperature -40°C~+75°C. 12/24/48 VDC & 24VAC (9.6~60 VDC & 18~30 VAC) power supply enter (Only connect to class 2 power).

제품 장점

- ☒ Unmanaged Industrial Switch made from Anti-Corrosion Aluminum Alloy.
- ☒ 5 10/100BaseT Ports.
- ☒ 12/24/48 VDC & 24VAC (9.6~60VDC & 18~30 VAC) Power Input
- ☒ Operating Temperature from -40°C to +75°C.
- ☒ IP30 Protection Class

제품 인증

기술 데이터

제품 도면

3D

□

interface

Port 1 Type	RJ45
Number of ports 1	5
Transmission rate	10/100 Mbps

Mechanical structure

Shell material	Die-cast aluminum alloy housing
switch	QoS function, BSP (Broadcast Storm Protection) function
Installation method	Card rail installation
Protection class	IP30

exchange property

MAC table size	4K
Bandwidth backplane	16Gbps
packet buffer	1.5Mb

MTBF

Standards compliant	Telcordia SR-332
operating hours	≥38,7641H

Warranty

Warranty	5 years
----------	---------

power supply

Supply voltage range	9.6~60VDC & 18~30VAC
reverse voltage protection	support
Connection Type	2P plug-in terminal
connecting wire diameter	0.5~1.5mm/ 28~16AWG
Overcurrent protection	support
Input voltage	12/24/48 VDC & 24 VAC

Environmental data

working altitude	≤2000m
Operating temperature	-40°C~+75°C
storage temperature	-40°C~+85°C
humidity	5% ~ 95% (non-condensing)

Dimension

high	100mm
length	61.8mm
width	24mm

약세사리

비즈니스 데이터	
발주 번호	30090000001
포장 단위	1 STK
MOQ	1 STK
제품 무게 (포장 제외)	170g