


총람

제품 장점



2EDGRC-THR-5.08-10030001778

Pluggable Terminal Blocks nominal current 20A. Rated voltage (III/3): 320V, pitch: 5.08mm, Color: black, Contact surface: Tin

제품 장점

- ☒ Suitable for SMT welding process
- ☒ The plug direction is parallel to the PCB, Can meet the needs of different connectors

제품 인증



기술 데이터

제품 도면

3D

□

Processing notes

Process

Reflow soldering/wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated current	20A

Rated current(III/2)	320V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	5.08mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~130℃
---------------------------------	-----------

악세사리

Tool

Screwdriver	/
Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/

비즈니스 데이터	
발주 번호	10030001778
포장 단위	
MOQ	
제품 무게 (포장 제외)	