

총람

제품 장점



15EDGKNHG-3.5-10020000445

Pluggable Terminal Blocks nominal current 9.5A. Rated voltage (II/2): 320V, pitch: 3.5mm, Color: green, Contact surface: Tin

제품 장점

- ☑ Adapt to multi-type sockets, device design is highly flexible
- ☑ PUSH-IN connection technology, fast wiring
- ☑ High-density double row, compact structure

제품 인증



기술 데이터

제품 도면

3D

□

Connection capacity

Conductor cross section solid	0.2~1.5mm ²
Conductor cross section flexible	0.2~1.5mm ²
AWG	26~16AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	8A
Rated current (C)	8A

Electrical parameters IEC

Rated voltage	250V
Rated current(III/3)	200V
Rated current	9.5A
Rated current(III/2)	250V
Rated current(II/2)	320V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	0°
Connection method	Push-in spring connection
Pitch	3.5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)

-40℃~105℃

악세서리

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	15EDGKNH-PWI

비즈니스 데이터

발주 번호	10020000445
포장 단위	
MOQ	
제품 무게 (포장 제외)	